

MODEL

GC20698-1/-2 系列

长臂型综合送料厚料平缝机

LONG ARM HEAVY DUTY COMPOUND FEED
LOCKSTITCHER

- GC20698-1**
- GC20698-1-D**
- GC20698-1L**
- GC20698-2**
- GC20698-2-D**
- GC20698-2L**



GC20698-2 长臂型综合送料厚料双针平缝机



本机是海菱 GC20618 的改进型。超长型缝台，使操作空间更为广阔。压脚提升装置分为手动和脚踏板控制，梭芯绕线装置位于机头中部上方，使操作显得轻松自如。整机在综合性能上保持了传动轻滑、噪音小、耐用度高的特点。适用于汽车罩、坐垫、安全带、帐篷、降落伞、滑翔伞、船帆等大型物品的缝制。

GC20698-1/-2 型单针 / 双针长臂型综合送料厚料平缝机
GC20698-1-D/-2-D 型单针 / 双针长臂型自动剪线综合送料厚料平缝机

GC20698-1L/-2L 型单针 / 双针长臂型综合送料厚料平缝机 (气动抬压脚)



This model is derived from GC20618. The long arm flat bed gives a wider working space. The presser foot can be lifted manually or by foot treadle. The bobbin winder on top and in middle of the machine head makes the sewing operation very easy. It features smooth machine running, low noise and machine durability, available for stitching car covers, car seats, safety belts, tents, parachutes, gliding parachutes, sails and other large workpiece.

GC20698-1/-2 Single needle/twin-needle long arm heavy duty compound feed lockstitcher.

GC20698-1-D/-2-D Single needle/twin-needle long arm heavy duty compound feed lockstitcher with auto thread trimmer.

GC20698-1L/-2L Single needle/twin-needle long arm heavy duty compound feed lockstitcher (Pneumatic footlifter).

特殊规格针间距请在订货时指定
Please specify for special needle gauge when ordering



型号 Model	GC20698 -1	GC20698 -1-D	GC20698 -1L	GC20698 -2	GC20698 -2-D	GC20698 -2L
最高缝速 Max. sewing speed	1800 r.p.m.					
线迹长度 Stitch length	0-9 mm					
针杆行程 Needle bar stroke	36 mm					
挑线杆行程 Thread take-up stroke	74.5 mm					
压脚提升 Presser foot lift	手动 By hand	8 mm	气动 16 mm	8 mm	气动 16 mm	气动 16 mm
	脚控 By foot	16 mm	16 mm Pneumatic	16 mm	16 mm Pneumatic	16 mm Pneumatic
机针 Needle size	DP × 17 18 [#] -23 [#]					
机针数 Needle numbers	1			2		
旋梭 Rotating hook	大型立式 旋梭 Large hook	大型自动 剪线旋梭 Large hook for trimmer	大型立式 旋梭 Large hook	大型立式 旋梭 Large hook	大型自动 剪线旋梭 Large hook for trimmer	大型立式 旋梭 Large hook
润滑方式 Lubrication	手工润滑 Manually lubricated					
安全离合装置 Safety clutch device	✓			✓		
针间距 Needle gauge	—			标准6.4mm 特缝3.2 4.8 6 9.5 12.7 16 19 25.4 mm Standard 6.4mm special 3.2 4.8 8 9.5 12.7 16 19 25.4 mm		25.4 31.8mm
电动机 Motor	370 瓦 1400 转 / 分 370W 1400r.p.m.	220 伏 750 瓦 伺服电机 220V750W Servo motor	370 瓦 1400 转 / 分 370W 1400r.p.m.	220 伏 750 瓦 伺服电机 220V750W Servo motor		
操作空间 Working space	635mm · 100mm	1000 mm × 100 mm	635mm · 100mm	1000 mm × 100 mm		