

MODEL

GC188 系列

高速单针平缝机

HIGH SPEED SINGLE NEEDLE LOCKSTITCH SEWING MACHINE

GC188-M

GC188-H

GC188-B





GC188-H 高速单针平缝机

Highlead Canada
www.highleadcanada.com



本系列单针平缝机外形采用最新设计。机器运转时的噪音和振动得到了较好的抑制。采用连杆式送料机构和连杆挑线，旋梭勾线、构成双线锁式线迹。上下轴用螺旋伞齿轮传动，圆盘式针距调节机构、杠杆式倒顺缝机构、全自动润滑。线迹平整，高低速缝纫、倒顺缝针距误差小。GC188-H型、GC188-B型适用于缝制各种皮革，帆布等中厚料物品。GC188-HL型，GC188-BL型由于配用了滚轮压脚，因此更适宜于中厚型布袋、鞋面、座垫、床罩等物品的缝制。

This series is designed with a new appearance, link-type feeding mechanism, link thread take-up, hook thread catching, bevel gear driving, dial stitch regulating, lever reverse feeding and automatic lubrication. And it features low noise, low vibration, and uniform stitches whether in forward feeding or in reverse feeding. The submodels GC188-H and GC188-B are available for sewing various kinds of leather, canvas, etc. And the submodels GC188-HL and GC188-BL are equipped with roller presser foot, so they can sew heavy weight baggage, shoe-upper, seat cushion and bed-covers.



型号 Model	GC188-M	GC188-H	GC188-B	GC188-HL	GC188-BL
最高缝速 Max. sewing speed	5000r.p.m.	3500r.p.m.	3000r.p.m.	3500r.p.m.	3000r.p.m.
线迹长度 Stitch length	0-5 mm	0-7 mm	0-8 mm	0-7 mm	0-8 mm
针杆行程 Needle bar stroke	31.8 mm	35 mm	35 mm	35 mm	35 mm
压脚提升 Presser foot lift	手动 By hand	5.5 mm	6 mm	6 mm	6 mm
	膝控 By knee	13 mm	13 mm	13 mm	13 mm
机针 Needle size	DB × 1 9 [#] -16 [#]	DP × 5 18 [#] -24 [#]	DP × 5 18 [#] -24 [#]	DP × 5 18 [#] -24 [#]	DP × 5 18 [#] -24 [#]
送布牙 Feed dog	3 列齿 3 rows of teech			φ 15 滚轮压脚 φ 15 Roller presser foot	
旋梭 Rotating hook	全自动润滑旋梭 Auto lubricated hook		全自动 润滑大旋梭 Auto lubricated large hook	全自动 润滑旋梭 Auto lubricated hook	全自动 润滑大旋梭 Auto lubricated large hook
润滑方式 Lubrication	自动润滑 Auto lubricated				
电动机 Motor	370 瓦缝纫机专用电机 370W Clutch motor				